



EPDM has excellent ozone, chemical and ageing characteristics. It that can be used as a gasket seal, flooring, table top and in machine and auto-repair workshops. It is also suited to marine applications, where acids or chemicals are present and exposure to natural elements is high.



SIZE INFORMATION

- Thickness Rang(mm): 0.5~25
- Width Range(m): 1~1.5
- Length Range(m): 1~20
- Colour: Black and off-white (for FG)

APPLICATION

- Seals and gaskets
- Matting for protection purpose
- Table top
- Outdoor Use
- Special requirements workshop

BASIC INFORMATION

- Temperature range (°C): -25~+130
- Tensile strength range (Mpa): 4.9~14
- Elongation at break range (%): 250~400
- Specific gravity (kg/cm³): 1.15~1.35
- Hardness range (SHORE A): 50~70
- Compression set range*: 8~45

FEATURE

- Excellent Ozone
- Excellent chemical-resistance
- Anti-aging property
- Good water-resistance

GRADE

- Commercial Grade Rubber Sheets
- Special Grade EPDM Rubber Sheet
- Food Grade Rubber Sheet

NOTE

- One side or both side smooth or fabric finish can be supplied.
- Specifications are subject to change without notice
- * Compression Set at 70°C for 22 hrs.