



Hypalon(CSM) Rubber sheet has high-temperature resistance and chemical resistance to acids and alkalis. CSM (Hypalon) Rubber Sheet has good physical and flame resistant properties, making it suitable for electrical sealing applications.



## SIZE INFORMATION

- Thickness Rang(mm): 0.5~25
- Width Range(m): 1~1.5
- Length Range(m): 1~10
- Colour: Black

## APPLICATION

- Seals and flange gaskets
- Lining of pipes and tanks
- Transfer and joining sleeves
- Insulating strip & Isolation barriers
- Acid proof Splash guards and covers

## BASIC INFORMATION

- Temperature range (°C): -35~+140
- Tensile strength range (Mpa): 6.8~15.5
- Elongation at break range (%): 350~400
- Specific gravity (kg/cm<sup>3</sup>): 1.30~1.40
- Hardness range (SHORE A): 60~70
- Compression set range\*: 35~40

## FEATURE

- Good Ozone resistance
- High temperature resistance
- Good Chemical resistance to acids and alkalis.
- Good Flame resistance

## GRADE

- Premium Grade Rubber Sheets

## NOTE

- One side or both side smooth or fabric finish can be supplied.
- Specifications are subject to change without notice
- \* Compression Set at 70°C for 22 hrs.