



SBR has good physical properties including good resistance to abrasion. However it is not recommended for use with oil, petroleum based products and organic solvent



SIZE INFORMATION

- Thickness Rang(mm): 0.5~25
- Width Range(m): 1~1.5
- Length Range(m): 1~20
- Colour:
Black~Beige~Honey~Grey~Red~Pink

APPLICATION

- Seals and gaskets
- Matting for protection purpose
- Skirt-board sheets
- Shot blasting sheets
- General Usage

BASIC INFORMATION

- Temperature range (°C): -20~+80
- Tensile strength range (Mpa): 1.5~20
- Elongation at break range (%): 350~800
- Specific gravity (kg/cm³): 0.98~2.10
- Hardness range (SHORE A): 35~75
- Compression set range*: 30~55
- Abrasion resistant range: 150~350

FEATURE

- Good abrasion- resistance
- Good tensile strength
- Anti-aging property

GRADE

- Commercial Grade
- Abrasion Resistant Rubber Sheets
- SBR Food Grade Rubber Sheets
- Multi Purpose Rubber Sheets

NOTE

- Sheets can be supplied with 1 or 2 ply insertion/s in Cotton, Nylon, Polyester, Glass Fibre etc.
- One side or both side smooth or fabric finish can be supplied.
- Specifications are subject to change without notice.
- * Compression Set at 70°C for 22 hrs.